



性能:
 额定电流: 3A
 额定电压: 30V
 耐电压: 500V
 接触电阻: 30mΩ
 绝缘电阻: 500MΩ
 工作温度: -55℃~+125℃
 塑件(材质): PA9T
 接触点(材质): 磷铜, 镀金5U

Pin	PART NO.	DIM A	DIM B
2P	BC-1-207	7.7	5.11
3P	BC-1-317	11.7	9.11
4P	BC-1-410	15.7	13.11
5P	BC-1-502	19.7	17.11
6P	BC-1-604	23.7	21.11

2	HOUSING	PA9T	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-097	
PART NO.		BC-1-207/317/410/502/604		CHECK		Q.L.Doi		REV.		A0	
UNIT :		TOLERANCE		ANGLE		APPROVAL		DATE		26-08-2017	
mm		OTHERWISE		0°±3'		SCALE		PAGE		1 OF 1	
		UP TO 5 ±0.2				2:1					
		ABOVE 5 30 ~ ±0.3									
		ABOVE 30 ±0.5									
		±0.3									