



性能:
 额定电流: 2.0A
 额定电压: 12V
 耐电压: 500V
 接触电阻: 30mΩ
 绝缘电阻: 500MΩ
 工作温度: -40℃~+85℃
 塑件(材质): LCP
 接触点(材质): 磷铜, 触点镀金3U"

PART NO.	DIM A	DIM B						
BC-1-412	4.0	5.90±0.2	2	HOUSING	LCP	1	BLACK	
BC-1-412A	4.5	6.40±0.2	1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED	
BC-1-412B	5.5	7.40±0.2	NO.	PARTS	MATERIAL	QTY.	FINISHING	

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-103	
PART NO.		BC-1-412 412A 412B		CHECK		Q.L.Dai		REV.		A0	
UNIT : mm	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE		30-08-2017			
	OTHERWISE	ABOVE 5 30 ~	±0.3		SCALE	2:1		PAGE		1 OF 1	