


RECOMMENDED PCB LAYOUT
TOP VIEW(.XX±0.05)



性能：
 额定电流：2.0A
 额定电压：12V
 耐电压：500V
 接触电阻：30mΩ
 绝缘电阻：500MΩ
 工作温度：-40℃~+85℃
 塑件（材质）：LCP
 接触点（材质）：磷铜，镀金

Pin(N)	PART NO.	DIM A
2Pin	BC-1-208	4.0
3Pin	BC-1-319	6.0
4Pin	BC-1-413	8.0
5Pin	BC-1-505	10.0
6Pin	BC-1-606	12.0
7Pin	BC-1-701	14.0
8Pin	BC-1-801	16.0

2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-230
PART NO.		BC-1-208/319/413/505/606/701/801		CHECK	Q.L..Dai	REV.	A0
UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	15-08-2017
		ABOVE 5 TO 30	±0.3				
mm		ABOVE 30	±0.5	0°±3'	SCALE	PAGE	1 OF 1
		ANGLE	±3'				