



性能:

额定电流: 5.0A

额定电压: 30V

耐电压: 500V

接触电阻: 50mΩ Max

绝缘电阻: 500MΩ Min

工作温度: -40℃~+85℃

塑件(材质): LCP

接触点(材质): 磷铜, 触点镀金3U"

使用寿命: 5000次以上

PIN(N)	PART NO.	DIM A	DIM B	DIM C
3Pin	BC-1-331	12.75	4.25	8.5
4Pin	BC-1-418	17.0	8.5	12.75
5Pin	BC-1-506	21.25	12.75	17.0
6Pin	BC-1-607	25.5	17.0	21.25

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-110
PART NO.		BC-1-331/418/506/607		CHECK	Q.L.Dai	REV.	A0
UNIT :	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	15-08-2019
mm	OTHERWISE	ABOVE 5 30	±0.3	0°±3'	SCALE	PAGE	1 OF 1
		ABOVE 30	±0.5		2:1		
		ANGLE	±3'				