



一般尺寸公差: ± 0.05
PCB 布线图

性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 镀金

| | | | | |
|-----|------------------|-----------------|------|-----------|
| 2 | HOUSING | LCP | 1 | BLACK |
| 1 | CONTACT TERMINAL | Phosphor bronze | 3 | Au PLATED |
| NO. | PARTS | MATERIAL | QTY. | FINISHING |

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

| | | | | | | | |
|-----------|-----------|------------|-----------|---------------------------|----------|---------|------------|
| PART NAME | | CONNECTOR | | DRAWING | G.B.Wu | DWG.No. | DS-BC-026 |
| PART NO. | | BC-4-401 | | CHECK | Q.L..Dai | REV. | A0 |
| UNIT : | TOLERANCE | UP TO 5 | ± 0.2 | ANGLE | APPROVAL | DATE | 28-03-2017 |
| | | ABOVE 5 30 | ± 0.3 | | | | |
| mm | OTHERWISE | ABOVE 30 | ± 0.5 | $0^{\circ} \pm 3^{\circ}$ | SCALE | PAGE | 1 OF 1 |