



性能:

- 额定电流: 5.0A
- 额定电压: 30V
- 耐压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -55℃~+125℃
- 使用寿命: 10000次以上
- 塑件(材质): LCP黑色
- 接触点(材质): 黄铜C2680, 镀金

PART NO.	DIM A	DIM B
BC-0-203	8.0	6.0
BC-0-304	12.0	10.0
BC-0-403	16.0	14.0
BC-0-503	20.0	18.0
BC-0-602	24.0	22.0

2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHORUS COPPER	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME	CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-175
PART NO.	BC-0-203 304 403 503 602		CHECK	Q.L.Dai	REV.	A0
	UNIT :	TOLERANCE	APPROVAL	DATE	29-06-2018	PAGE
	mm	OTHERWISE				
		UP TO 5 ±0.2	SCALE	2:1	PAGE	1 OF 1
		ABOVE 5 30 ~ ±0.3				
		ABOVE 30 ±0.5				
		ANGLE ±3°				