



性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 镀金

PART NO.	DIM A	DIM B	DIM C
BC-2-338	8.0±0.15	5.9±0.3	6.9±0.3
BC-2-338A	9.0±0.15	6.9±0.3	7.9±0.3
BC-2-338B	10.0±0.15	7.9±0.3	8.9±0.3

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-231
PART NO.		BC-2-338/338A/338B		CHECK	Q.L..Dai	REV.	A0
UNIT :	TOLERANCE	UP TO 5	±0.2	APPROVAL	DATE	15-08-2017	1 OF 1
		ABOVE 5 TO 30	±0.3				
mm	OTHERWISE	ABOVE 30	±0.5	SCALE	2:1	PAGE	1 OF 1
		ANGLE	0°±3'				