



RECOMMENDED PCB LAYOUT
TOL: (± 0.05)

性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 触点镀金3U"
- 使用寿命: 3000次以上

PART NO.	DIM A	DIM B	DIM C
BC-2-370	9.0	5.0	2.5
BC-2-410	11.5	7.5	5.0
BC-2-502	14.0	10.0	7.5
BC-2-602	16.5	12.5	10.0

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHORUS COPPER	3	Au PLATED

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DS-BC-175	
PART NO.		BC-2-370 410 502 602		CHECK		Q.L.Dai		REV. A0	
UNIT		TOLERANCE		ANGLE		APPROVAL		DATE	
mm		OTHERWISE		0°±3'		SCALE		PAGE	
		UP TO 5 ±0.2				2:1		1 OF 1	
		ABOVE 5 30 ~ ±0.3							
		ABOVE 30 ±0.5							
		±0.3							