



性能:

额定电流: 5.0A

额定电压: 30V

耐电压: 500V

接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -55℃~+125℃

使用寿命: 10000次以上

塑件(材质): LCP黑色

接触点(材质): 黄铜C2680, 接触面镀金3U"

RECOMMENDED PCB LAYOUT
TOP VIEW (.XX±0.05)

规格	DIM A	DIM B
BC-0-205	6.0	3.0
BC-0-307	9.0	6.0
BC-0-407	12.0	9.0
BC-0-505	15.0	12.0
BC-0-605	18.0	15.0
BC-0-703	21.0	18.0
BC-0-803	24.0	21.0

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	BRASS	3	Au PLATED

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-132	
PART NO.		BC-0-205 307 407 505 605 703 803		CHECK		Q.L.Dai		REV.		A0	
UNIT		TOLERANCE		ANGLE		APPROVAL		DATE		08-05-2021	
mm		OTHERWISE		0°±3'		SCALE		PAGE		1 OF 1	
		UP TO 5 ±0.2				2:1					
		ABOVE 5 30 ~ ±0.3									
		ABOVE 30 ±0.5									
		ANGLE ±3'									