



剖面 A-A

RECOMMENDED PCB LAYOUT
TOP VIEW (. XX±0.05)

- 性能:
- 额定电流: 1.0A
 - 额定电压: 12V
 - 耐电压: 500V
 - 接触电阻: 30mΩ 以内
 - 绝缘电阻: 500MΩ
 - 工作温度: -40℃~+85℃
 - 塑件 (材质): LCP 黑色
 - 接触点 (材质): 铜合金, 触点镀金3U"

2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-113	
PART NO.		BC-1-428		CHECK		Q.L.Dai		REV.		A0	
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	PAGE	09-07-2022	1 OF 1		
		ABOVE 5 30 ~	±0.3							0°±3'	
		ABOVE 30	±0.5		SCALE	2:1					

COPYRIGHT RESERVED, PLEASE DO NOT COPY.