



REV.	DESCRIPTION	DRAW.	DATE.

- NOTE:
- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: C2680
 - FINISH:
 - TERMINAL: NICKEL 50 μm MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
 - PRODUCT SPECIFICATION
 - CURRENT RATING : 5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE: 500VAC
 - INSULATION RESISTANCE: 100MΩ min.
 - CONTACT RESISTANCE: 30mΩ Max.
 - Operating Temperature: -40° ~105°

RECOMMENDED PCB LAYOUT
 T=1.2MM, TOLERANCES ±0.05MM

东莞市朗顿电子科技有限公司

UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. i∆0.5 X.x i∆0.35 X.xx i∆0.25 ANGULAR i∆2i∆	DESIGN	W.J.H	DATE	2017.05.26	TITLE:	
	APPROVED		DATE		LD-A01M-A-13P-M5	
	PART NO		REV:	01	SCALE:	1:1
	DRAWING NO		SIZE:	A4	SHEET:	1/1
						UNIT: MM

