



性能:

- 额定电流: 3.0A
- 额定电压: 24V
- 耐电压: 500V
- 接触电阻: 30mΩ MAX
- 绝缘电阻: 500MΩ
- 工作温度: -40°C ~ +85°C
- 塑件(材质): LCP, 耐高温260°C
- 接触点(材质): 铜合金, 触点镀金3U

PART NO.	DIM A	DIM B
BC-2-240A	8.0	3.0
BC-2-372A	11.0	6.0
BC-2-412A	14.0	9.0
BC-2-505A	17.0	12.0
BC-2-605A	20.0	15.0

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHORUS COPPER	3	Au PLATED

东莞市朗顿电子科技有限公司

PART NAME	CONNECTOR		DRAWING	G.B.Wu	DWG.No.	LD-BC-230
PART NO.	BC-2-240A 372A 412A 505A 605A		CHECK	Q.L.Dai	REV.	A0
UNIT	mm	TOLERANCE	APPROVAL	DATE	15-08-2021	
		UP TO 5 ±0.2	SCALE	2:1	PAGE	1 OF 1
		ABOVE 5 30 ~ ±0.3				
		ABOVE 30 ±0.5				
		OTHERWISE ±3°				

COPYRIGHT RESERVED, PLEASE DO NOT COPY.