



性能：
 额定电流：3.0A
 额定电压：12V
 耐电压：500V
 接触电阻：30mΩ MAX
 绝缘电阻：500MΩ
 工作温度：-40℃~+85℃
 塑件（材质）：LCP黑色
 接触点（材质）：铜合金，触点镀金3U”

PART NO.	DIM A	DIM B	DIM C	NO.	PARTS	MATERIAL	QTY.	FINISHING
BC-2-301	8.0	5.70±0.3	6.85±0.3	2	HOUSING	LCP	1	BLACK
BC-2-301A	9.25	6.95±0.3	8.10±0.3	1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED
BC-2-301B	10.50	8.20±0.3	9.35±0.3	NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司 PART NAME: CONNECTOR PART NO.: BC-2-301 301A 301B		DRAWING		G.B.Wu	DWG.No.	DS-BC-85
		CHECK	Q.L.Dai	REV.	A0	
UNIT : mm TOLERANCE : OTHERWISE	UP TO 5	±0.2	ANGLE : 0°±3'	APPROVAL	DATE	03-09-2012
	ABOVE 5 ~ 30	±0.3		SCALE	2:1	PAGE
	ABOVE 30	±0.5				
	ANGLE	±3'				

COPYRIGHT RESERVED, PLEASE DO NOT COPY.