



性能:
 额定电流: 3.0A
 额定电压: 12V
 耐电压: 500V
 接触电阻: 30mΩ MAX
 绝缘电阻: 500MΩ
 工作温度: -40℃~+85℃
 塑件(材质): LCP黑色
 接触点(材质): 铜合金, 触点镀金3U"

RECOMMENDED PCB LAYOUT
 TOP VIEW (.XX±0.05)

PART NO.	DIM A	DIM B	DIM C
BC-2-414-C01	8.0	5.70±0.3	6.85±0.3
BC-2-414A-C01	9.25	6.95±0.3	8.10±0.3
BC-2-414B-C01	10.50	8.20±0.3	9.35±0.3

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED

东莞市朗顿电子科技有限公司

PART NAME		CONNECTOR		DRAWING		G.B.Wu		DWG.No.		DS-BC-86	
PART NO.		BC-2-414 414A 414B-C01		CHECK		Q.L.Dai		REV.		A0	
UNIT		TOLERANCE		ANGLE		APPROVAL		DATE		03-09-2012	
mm		OTHERWISE		0°±3'		SCALE		PAGE		1 OF 1	
		UP TO 5 ±0.2				2:1					
		ABOVE 5 30 ~ ±0.3									
		ABOVE 30 ±0.5									
		ANGLE ±3'									

COPYRIGHT RESERVED, PLEASE DO NOT COPY.